


电特性/极限值 Electric speciality/limit value

符号	参数	参数值	单位
I_T	正向平均电流	200	A
V_{DRM}/V_{RRM}	断态/反向重复峰值电压	1200-1600	V
I_{GTMax}	控制极触发电流	60	mA
V_{GTMax}	控制极触发电压	1.5	V
I_{TSM}	通态不重复浪涌电流	2200	A
I_HMax	维持电流	120	mA
dv/dt	通态电压临界上升率	800	V/ μ s
di/dt	通态电流临界上升率	100	A/ μ s
V_{TM}	通态峰值电压	1.50	V
size	芯片尺寸	$\Phi 27$	mm



YUEQING LIUJING RECTIFIER CO., LTD

Sale Department: Liujing Building, Yueqing City,
Zhejiang Province

Add: Wanao Industrial Zone, Yueqing city,
Zhejiang Province

Tel: 0086-577-62519692 0089-577-62519693

Fax: 0086-577-62518692

International Export: 0086-577-62571902

Technical Support: 0086-15868768965

After Service: 400-6606-086

<http://www.china-liujing.com>

<http://www.liujingdianqi.cn>

<http://www.cnrectifier.com>

<http://www.cnthyristor.com.cn>

MSN: thristors@hotmail.com

打造最具竞争力的电力半导体产品

To be the most competitive Power Semiconductor
Devices manufactory.

LIUJING reserves the right to change limits, test conditions and dimensions.

윤정은 이 칼타로그 중에 데이트, 테스트 조건, 외형사이즈에 대한 최종 해석권을 가지고 있습니다.