

### FEATURES


- 1). Reverse voltages up to 1600V
- 2). Hermetic metal case with glass insulator
- 3). Threaded stud ISO M24 × 1.5
- 4). SKR: cathode to stud

### MAJOR RATINGS AND CHARACTERISTICS

$V_{RSM}$	$V_{RRM}$	$I_{FRMS}=700A$ (maximum value for continuous operation) $I_{FAV}=320A$ (sin. 180° ; $T_C=125^{\circ}C$ )
V	V	
400	400	SKR 320/04
800	800	SKR 320/08
1200	1200	SKR 320/12
1400	1400	SKR 320/14
1600	1600	SKR 320/16

### TYPICAL APPLICATIONS

- 1). All-purpose mean power rectifier diodes
- 2). Cooling via heatsinks
- 3). Non-controllable and half-controllable rectifiers
- 4). Free-wheeling diodes
- 5). Recommended snubber network:  
RC: 1  $\mu$ F, 20  $\Omega$  ( $P_R=2W$ ),  
 $R_p=25K \Omega$  ( $P_R=20W$ )



### ELECTRICAL SPECIFICATIONS

Symbol	Conditions	Values	V
$I_{FAV}$	sin. 180; $T_C=85(100)^{\circ}C$	445(420)	A
$I_D$	K 1/200; $T_a=45^{\circ}C$ ; B2/B6	480/690	A
	K 0.55F; $T_a=35^{\circ}C$ ; B2/B6	760/1080	A
$I_{FSM}$	$T_{vj}=25^{\circ}C$ ; 10ms	9000	A
	$T_{vj}=180^{\circ}C$ ; 10ms	8000	A
$I^2t$	$T_{vj}=25^{\circ}C$ ; 8,3 ... 10ms	400000	A <sub>2</sub> S
	$T_{vj}=180^{\circ}C$ ; 8,3 ... 10ms	300000	A <sub>2</sub> S
$V_F$	$T_{vj}=25^{\circ}C$ ; $I_F=1000A$	max. 1.35	V
$V_{(TO)}$	$T_{vj}=180^{\circ}C$	max. 0.8	V
$r_T$	$T_{vj}=180^{\circ}C$	max. 0.45	m $\Omega$
$I_{RD}$	$T_{vj}=180^{\circ}C$ ; $V_{RD}=V_{RRM}$	max. 100	mA
$Q_{rr}$	$T_{vj}=160^{\circ}C$ ; $-di_F/dt=10A \mu s$	300	$\mu C$
$R_{th(j-c)}$		0.16	K/W
$R_{th(c-s)}$		0.015	K/W
$T_{vj}$		-40 ... +180	$^{\circ}C$
$T_{stg}$		-55 ... +180	$^{\circ}C$

Symbol	Conditions	Values	V
$V_{isol}$		-	V~
$M_s$	to heatsink	60	Nm
a		5*9.81	m/s <sup>2</sup>
m	approx.	500	g
Case		E16	

**PERFORMANCE CURVES FIGURE**




Fig. 1L Power dissipation vs. forward current




Fig. 1R Power dissipation vs. ambient temperature




Fig. 2 Forward current vs. case temperature




Fig. 4 Transient thermal impedance vs. time




Fig. 5 Forward characteristics





Fig. 6 Surge overload current vs. time

**OUTLINE**



**SKD10**

**YUEQING LIUJING RECTIFIER CO., LTD**

Sale Department: Liujing Building, Yueqing City,  
Zhejiang Province

Add: Wanao Industrial Zone, Yueqing city,  
Zhejiang Province

Tel: 0086-577-62519692    0089-577-62519693

Fax: 0086-577-62518692

International Export: 0086-577-62571902

Technical Support: 0086-15868768965

After Service: 400-6606-086

<http://www.china-liujing.com>

<http://www.liujingdianqi.cn>

<http://www.cnrectifier.com>

<http://www.cnthyristor.com.cn>

MSN: [thristors@hotmail.com](mailto:thristors@hotmail.com)

**打造最具竞争力的电力半导体产品**

To be the most competitive Power Semiconductor  
Devices manufactory.

LIUJING reserves the right to change limits, test conditions and dimensions.

윤정은 이 칼타로그 중에 데이트, 테스트 조건, 외형사이즈에 대한 최종 해석권을 가지고 있습니다.